



Non-Tipping Trailer

Non Tipping trailers are fabricated with very high quality standards. Heavy Duty structured framework brings in greater strength and stability. The typical features like solid beam axle, good quality bearings and tyres, CNC machined hub enhance durability & reliability.

Technical Specifications			
	3 Ton (2WNT)	5 Ton (2WNT)	9 Ton (2WNT)
Tractor Power (HP)	40-50	50-70	70-90
Main Chassis	125x65 mm	150x75 mm	200x75 mm
Support Channel	75x40 mm	75x40 mm	75x40 mm
Floor Platform	4 mm Thickness	4 mm Thickness	4 mm Thickness
Side Wall	2 mm Thickness Corrugated	2 mm Thickness Corrugated	2 mm Thickness Corrugated
Outer Dimension	8'x6'x1.5'feet (2435x1828x460mm)	10'x6'x1.75'feet (3048x1828x534mm)	12'x6'x2'feet (3658x1828x610mm)
Weight	850 Kg (Approx.)	1015 Kg (Approx.)	1415 Kg (Approx.)

N.H.11, Jaipur-Sikar Road, Bus Stand, Rampura-Dabri, Jaipur - 303704, Rajasthan (India)

Phone: 01423-224521, Fax: +01423-224525, Mobile: +91-9829500660, +91-9829115072

E-mail: info@greenkingindia.com, Website: www.greenkingindia.com